## SPE RESPONSE FOR CERTIFICATE OF CORRECTION

		·	Paper No.:
	DATE	: <u>06/07/2007</u>	
	TO SPE OF	: ART UNIT 1700 (1755)	
SUBJECT: Request for Certificate of Correction on Patent No.: 7,160,837  Attn: Lynn Hailey		on Patent No.: <u>7,160,837</u>	
	A response is	requested with respect to the accon	npanying request for a certificate of correction.
	Please complete this form and return with file, within 7 days to:  Certificates of Correction Branch - PK 3-922  Palm location 7580 - Tel. No. 305-8309		
-	With respect to the change(s) requested, correcting Office and/or Applicant's errors, should the patent read as shown in the certificate of correction? No new matter should be introduced, nor should the scope or meaning of the claims be changed.		
	Ok to make	dependency change in claim 10	as requested in C of C?
	Thank You For	Your Assistance	Ernest C. White, LIE305-8339 Certificates of Correction Branch
	,	Tour Addistance	Certificates of Correction Branch
	The request	for issuing the above-identified	
•	The request	for issuing the above-identified	
	The request	for issuing the above-identified on the appropriate box.	d correction(s) is hereby:
•	The request	for issuing the above-identified on the appropriate box.  Approved	d correction(s) is hereby:  All changes apply.
	The request	for issuing the above-identified on the appropriate box.  Approved  Approved in Part	d correction(s) is hereby:  All changes apply.  Specify below which changes do not apply.
•	The request Note your decision	for issuing the above-identified on the appropriate box.  Approved  Approved in Part  Denied	d correction(s) is hereby:  All changes apply.  Specify below which changes do not apply.  State the reasons for denial below.
	The request Note your decision	for issuing the above-identified on the appropriate box.  Approved  Approved in Part  Denied	d correction(s) is hereby:  All changes apply.  Specify below which changes do not apply.  State the reasons for denial below.
-	The request Note your decision	for issuing the above-identified on the appropriate box.  Approved  Approved in Part  Denied	All changes apply.  Specify below which changes do not apply.  State the reasons for denial below.  Pended from Cl. 8 (one.
	The request Note your decision	for issuing the above-identified on the appropriate box.  Approved  Approved in Part  Denied  10 (org. cl. 26) de and was neve	All changes apply.  Specify below which changes do not apply.  State the reasons for denial below.  Pended from Cl. 8 (one.
	The request Note your decision	for issuing the above-identified on the appropriate box.  Approved  Approved in Part  Denied  10 (org. cl. 26) de and was neve	All changes apply.  Specify below which changes do not apply.  State the reasons for denial below.  Pended from Cl. 8 (one.

U.S. DEPARTMENT OF COMMERCE Patent and Trademark Office

PTOL-306 (REV. 7/03)

#### UNITED STATES PATENT AND TRADEMARK OFFICE

# **CERTIFICATE OF CORRECTION**

PATENT NO. 7,160,837

DATED

January 9, 2007

INVENTOR(S):

Norifumi HASEGAWA

It is certified that an error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 8, line 41 (claim 10, line 2), "8" should read - 13 -; and

Column 10, line 25 (claim 25, line 7), delete "insoluble".

Mailing address of sender:

Patent No. 7,160,837

No. of add'l copies @ .30 per page

Bacon & Thomas, PLLC 625 Slaters Lane 4th Floor Alexandria, Va. 22314 TEL (703) 683-0500 FAX (703) 683-1080

Ś. Patent No. 7,160,837

## IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Examiner: Patricia L. Hailey

**Art Unit: 1755** 

Norifumi HASEGAWA

Issued: January 9, 2007

Serial No.: 10/667,974

Filed: September 23, 2003

For: MIXED CONDUCTOR AND MIXED

CONDUCTOR PRODUCING METHOD )

Certificate

of Correction

### REQUEST FOR CERTIFICATE OF CORRECTION

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Sir:

It is respectfully requested that a Certificate of Correction per the attached be issued for the captioned patent.

Please note that claim 8 (original claim 21) and claim 10 (original claim 26) are redundant. Claim 10, presented as claim 26, was intended to depend from claim 2 which issued as claim 13.

A check in the amount of \$100.00 is submitted herewith to cover the fee required

by 37 CFR 1.20(a).

Respectfully submitted BACKAN & THOMAS. F

George A. Loud

Registration No. 25,814/2007 HBERNE 00000013 7160837

109.00 OP

Date: May 21, 2007

**BACON & THOMAS, PLLC** 625 Slaters Lane, 4th Floor Alexandria, Virginia 22314 Telephone: (703) 683-0500 Claims as issued

Appl. No. 10/667,974 Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

This listing of claims will replace all prior versions and listings of claims in the application.

#### Listing of Claims:

\*(currently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by at least one of covalent bonding, intercalation and inclusion so as not to dissolve in water.

(currently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material obtained by carbonizing an organic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by at least one of covalent bonding, intercalation and inclusion, and wherein said electron conductor portion is made of an inorganic material obtained by carbonizing an organic material.

2 (currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said electron conductor portion is obtained by carbonizing at least one organic compound selected from the group consisting of aliphatic hydrocarbons, aromatic hydrocarbons and derivatives of aliphatic hydrocarbons and aromatic hydrocarbons.

4(canceled).

Appl. No. 10/667,974 Amendment dated: October 6, 2005 Reply to OA of: June 6, 2005

- 3 (currently amended). The mixed conductor <u>in the form of a single material</u> according to claim 1, wherein said electron conductor <u>portion</u> is a carbonaceous material selected from the group consisting of graphite and carbon nanotubes.
- 4 S(currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said proton conductor portion contains at least one member selected from the group consisting of phosphorus-containing compounds, sulfur-containing compounds, carboxylic acids, and inorganic solid-state acids.
- Kourrently amended). The mixed conductor in the form of a single material according to claim 1, wherein the electron conductor portion is fixed to the proton conductor portion by a covalent bond.

8(canceled).

9(canceled).

Q(currently amended). The mixed conductor <u>in the form of a single material</u> according to claim 1, wherein said electron conductor <u>portion</u> has consecutive carbon-carbon bonds including a carbon-carbon double bond.

N(currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said electron conductor <u>portion</u> is obtained by carbonizing an organic compound having one of or both of a carbon-carbon double bond and a carbon-carbon triple bond.

8 17

12(currently amended). A method for producing a mixed conductor <u>in the form of a single material</u> comprising:

Appl. No. 10/667,974 Amendment dated: October 6, 2005 Reply to OA of: June 6, 2005

a first step of obtaining a high molecular precursor by polymerizing an organic compound having one of or both of a carbon-carbon double bond and a carbon-carbon triple bond with a proton conducting material; and

a second step of pyrolyzing the precursor obtained in the first step in an inert atmosphere.

22

(currently amended). A method for producing a mixed conductor in the form of a single material comprising:

a first step of obtaining a high molecular precursor by dispersing a proton conducting material into an organic compound polymer having one of or both of a carbon-carbon double bond and a carbon-carbon triple bond; and

a second step of pyrolyzing the precursor obtained in the first step in an inert atmosphere.

18

14 (previously presented). The mixed conductor producing method according to claim 17 12, wherein the organic compound having one of or both of the carbon-carbon double bond and the carbon-carbon triple bond is an aliphatic hydrocarbon or an aromatic hydrocarbon.

19 15(previously presented). The mixed conductor producing method according to claim
18 14, wherein said organic compound is at least one member selected from the group consisting of polyacetylene, resorcinol, phenol, phenylphenol, polyaniline, polypyrrole, polythiophene, phenylphosphonic acid, and phenylsilane alkoxide.

120 16(currently amended). The mixed conductor producing method according to claim 12, wherein said proton conducting material is at least one member selected from the group consisting of phosphoric acid, phosphates, sulfuric acid, sulfates, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconia zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

- $\chi$  (currently amended). A mixed conductor producing method wherein an organic compound having a  $\pi$  bond is dehydration-condensation polymerized and bound with a compound having movable protons to obtain a precursor having proton conduction, and [[an]] energy is applied to said precursor under an inert gas atmosphere to thereby impart electron conduction to the precursor.
- 18(currently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together to form a catalyst support insoluble which does not dissolve in water and a noble metal catalyst supported on said catalyst.
- 2/ 19(original). The mixed conductor producing method according to claim 12, comprising a third step of causing the precursor burned in the second step to support a noble metal catalyst.
- 25 20(currently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material obtained by carbonizing an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together to form a catalyst support insoluble which does not dissolve in water and a noble metal catalyst supported on said catalyst support.
- 21(currently amended). The mixed conductor in the form of a single material according to claim 1 wherein said electron conductor portion is selected from the group consisting of carbonaceous materials, gold, palladium, platinum, magnesium, lithium, titanium, and alloys thereof; and

the proton conductor <u>portion</u> is made of at least one member selected from the group consisting of carbonic acid, boric acid, phosphoric acid, phosphoric acid esters,

Appl. No. 10/667,974 Amendment dated: October 6, 2005 Reply to OA of: June 6, 2005

sulfuric acid, sulfuric acid esters, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.

9 82(currently amended). The mixed conductor in the form of a single material according to claim 24 wherein said electron conductor portion is a carbonaceous material.

23(currently amended). The mixed conductor in the form of a single material according to claim 8 wherein said proton conductor portion is formed of phosphoric acid groups and said carbonaceous material has a graphite structure.

24(currently amended). The mixed conductor in the form of a single material according to claim 2-wherein said proton conductor portion is at least one member selected from the group consisting of phosphoric acid, phosphates, sulfuric acid, sulfates, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.

25(currently amended). The mixed conductor in the form of a single material according

to claim 24 wherein said electron conductor <u>portion</u> has a graphite structure.

26(currently amended). The mixed conductor in the form of a single material according to claim wherein said electron conductor portion is selected from the group consisting of carbonaceous materials, gold, palladium, platinum, magnesium, lithium, titanium, and alloys thereof; and

the proton conductor <u>portion</u> is made of at least one member selected from the group consisting of carbonic acid, boric acid, phosphoric acid, phosphoric acid esters, sulfuric acid, sulfuric acid esters, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, <u>zirconia</u> <u>zirconium</u> oxide, tungstophosphoric acid, and tungstosilicic acid.

26

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

l1

27(currently amended). The mixed conductor in the form of a single material according to claim 26 wherein said electron conductor portion is a carbonaceous material.

- 12 28(currently amended). The mixed conductor in the form of a single material according to claim 27 wherein said proton conductor portion is formed of phosphoric acid groups and said carbonaceous material has a graphite structure.
  - 26 29(currently amended). The mixed conductor in the form of a single material according to claim 20 wherein said proton conductor portion is at least one member selected from the group consisting of phosphoric acid, phosphates, sulfuric acid, sulfates, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.
  - 27 30(currently amended). The mixed conductor in the form of a single material according to claim 29 wherein said electron conductor portion has a graphite structure.
  - 18 31(new). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by intercalation so as not to dissolve in water.
- અ 32(new). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by inclusion so as not to dissolve in water.

Claims if Cl. 26 had been amended to depend from. Cl. 2

Appl. No. 10/667,974

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

This listing of claims will replace all prior versions and listings of claims in the application.

#### Listing of Claims:

(currently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by at least one of covalent bonding, intercalation and inclusion so as not to dissolve in water.

2 (currently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material obtained by carbonizing an organic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by at least one of covalent bonding, intercalation and inclusion, and wherein said electron conductor portion is made of an inorganic material obtained by carbonizing an organic material.

B. 3(currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said electron conductor portion is obtained by carbonizing at least one organic compound selected from the group consisting of aliphatic hydrocarbons, aromatic hydrocarbons and derivatives of aliphatic hydrocarbons and aromatic hydrocarbons.

4(canceled).

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

3

(currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said electron conductor <u>portion</u> is a carbonaceous material selected from the group consisting of graphite and carbon nanotubes.

4

6(currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said proton conductor <u>portion</u> contains at least one member selected from the group consisting of phosphorus-containing compounds, sulfur-containing compounds, carboxylic acids, and inorganic solid-state acids.

(currently amended). The mixed conductor in the form of a single material according to claim 1, wherein the electron conductor portion is fixed to the proton conductor portion by a covalent bond.

8(canceled).

9(canceled).

- (currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said electron conductor portion has consecutive carbon-carbon bonds including a carbon-carbon double bond.
- Th(currently amended). The mixed conductor in the form of a single material according to claim 1, wherein said electron conductor portion is obtained by carbonizing an organic compound having one of or both of a carbon-carbon double bond and a carbon-carbon triple bond.
- 17 \*2(currently amended). A method for producing a mixed conductor in the form of a single material comprising:

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

a first step of obtaining a high molecular precursor by polymerizing an organic compound having one of or both of a carbon-carbon double bond and a carbon-carbon triple bond with a proton conducting material; and

a second step of pyrolyzing the precursor obtained in the first step in an inert atmosphere.

23 13(currently amended). A method for producing a mixed conductor in the form of a single material comprising:

a first step of obtaining a high molecular precursor by dispersing a proton conducting material into an organic compound polymer having one of or both of a carbon-carbon double bond and a carbon-carbon triple bond; and

a second step of pyrolyzing the precursor obtained in the first step in an inert atmosphere.

- 14 (previously presented). The mixed conductor producing method according to claim
  12 wherein the organic compound having one of or both of the carbon-carbon double
  bond and the carbon-carbon triple bond is an aliphatic hydrocarbon or an aromatic
  hydrocarbon.
- 1 9 15(previously presented). The mixed conductor producing method according to claim wherein said organic compound is at least one member selected from the group consisting of polyacetylene, resorcinol, phenol, phenylphenol, polyaniline, polypyrrole, polythiophene, phenylphosphonic acid, and phenylsilane alkoxide.
- Me(currently amended). The mixed conductor producing method according to claim 12, wherein said proton conducting material is at least one member selected from the group consisting of phosphoric acid, phosphates, sulfuric acid, sulfates, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconia zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

- 23 1%(currently amended). A mixed conductor producing method wherein an organic compound having a  $\pi$  bond is dehydration-condensation polymerized and bound with a compound having movable protons to obtain a precursor having proton conduction, and [[an]] energy is applied to said precursor under an inert gas atmosphere to thereby impart electron conduction to the precursor.
- 24 Securrently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together to form a catalyst support insoluble which does not dissolve in water and a noble metal catalyst supported on said catalyst.
- 2/ 19(original). The mixed conductor producing method according to claim 12, comprising a third step of causing the precursor burned in the second step to support a noble metal catalyst.
- 25 28(currently amended). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material obtained by carbonizing an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together to form a catalyst support insoluble which does not dissolve in water and a noble metal catalyst supported on said catalyst support.
  - 24(currently amended). The mixed conductor <u>in the form of a single material</u> according to claim 1 wherein said electron conductor <u>portion</u> is selected from the group consisting of carbonaceous materials, gold, palladium, platinum, magnesium, lithium, titanium, and alloys thereof; and

the proton conductor <u>portion</u> is made of at least one member selected from the group consisting of carbonic acid, boric acid, phosphoric acid, phosphoric acid esters,

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

sulfuric acid, sulfuric acid esters, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.

- 7 22(currently amended). The mixed conductor in the form of a single material according to claim 21 wherein said electron conductor portion is a carbonaceous material.
- (currently amended). The mixed conductor in the form of a single material according to claim 2 wherein said proton conductor portion is formed of phosphoric acid groups and said carbonaceous material has a graphite structure.
- 24(currently amended). The mixed conductor in the form of a single material according to claim 2 wherein said proton conductor portion is at least one member selected from the group consisting of phosphoric acid, phosphates, sulfuric acid, sulfates, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.
- 25(currently amended). The mixed conductor in the form of a single material according to claim 24 wherein said electron conductor portion has a graphite structure.
- 26(currently amended). The mixed conductor in the form of a single material according to claim 25 wherein said electron conductor portion is selected from the group consisting of carbonaceous materials, gold, palladium, platinum, magnesium, lithium, titanium, and alloys thereof; and

the proton conductor <u>portion</u> is made of at least one member selected from the group consisting of carbonic acid, boric acid, phosphoric acid, phosphoric acid esters, sulfuric acid, sulfuric acid esters, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, <u>zirconia</u> <u>zirconium</u> oxide, tungstophosphoric acid, and tungstosilicic acid.

Amendment dated: October 6, 2005

Reply to OA of: June 6, 2005

23 (currently amended). The mixed conductor in the form of a single material according to claim 26 wherein said electron conductor portion is a carbonaceous material.

- 28(currently amended). The mixed conductor in the form of a single material according to claim 27 wherein said proton conductor portion is formed of phosphoric acid groups and said carbonaceous material has a graphite structure.
- 29(currently amended). The mixed conductor in the form of a single material according to claim 20 wherein said proton conductor portion is at least one member selected from the group consisting of phosphoric acid, phosphates, sulfuric acid, sulfates, tungsten oxide hydroxide, rhenium oxide hydroxide, silicon oxide, tin oxide, zirconium oxide, tungstophosphoric acid, and tungstosilicic acid.
- 2 730(currently amended). The mixed conductor <u>in the form of a single material</u> according to claim 20 wherein said electron conductor <u>portion</u> has a graphite structure.
- (new). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by intercalation so as not to dissolve in water.
- 29 32(new). A mixed conductor in the form of a single material comprising an electron conductor portion made of an inorganic material and a proton conductor portion made of an inorganic material, said electron conductor portion and said proton conductor portion being fixed together by inclusion so as not to dissolve in water.